



DATASIGN PORTABLE BOOM GATE

Datasign Portable Boom Gate.



Key Fob



Back inside view



Built in charger

Removable batteries

Options



Traffic Light



Remote Control



Solar



www.datasigns.com



1300 850 785





DATA SIGN PORTABLE BOOM GATE

SPECIFICATIONS

Unit Dimensions	
Height	1100mm (1180mm including Handle and Aerial)
Width	300mm (380mm with Light option fitted)
Depth	370mm Including Boom (440mm including Handle)
Depth Setup with stabiliser arm extended	800mm
Weight: Main Unit	35Kg (Basic unit – not including, Batteries, Ballast or options fitted)
Boom Gate	6.5Kg
Battery Weight	15Kg Each – Total 30Kg
Total System Weight including Ballasts & Optional Light & Target Board fitted	155Kg

Basic Model Inclusions
Boom – 2.5 meter length – expandable to 4 meters with RED/GREEN LED bar, STOP SIGN.
Vehicle Detector – to stop boom lowering if vehicle under boom.
2 x 40AH AGM Batteries (weight 15Kg each)
240V AC, 24V 10A Mains Battery Charger
2 x Key FOB Remotes

Options
4 x 20Kg Ballast – to provide greater stabilization
PTL Trailer & PTL Compact interface – connects via direct link cable or RF.
PTL ST-1 Smart Remote Controller
Traffic Light fitted to Boom Gate Option – Australian Standards Traffic Light.
Traffic Light Target Board
PTL-Boom Gate Solar option. 200W 36V Foldable solar panel – sits on ground

